## 562 Sanitop™ Black







- Resilient rubber to provide fatigue relief made of tough compound, designed to yield a long service life.
- Moulded bevelled edges on all 4 sides for trip resistant & easy cart access.
- Lightweight facilitates handling when cleaning.
- Drainage holes and raised studs provide aeration and allow fluids and debris to fall through, keeping the surface clear.
- Aggressive slip resistant surfaces.
- Free of silicone therefore safe for vehicle painting facilities.
- Ergonomic benefit of 12.7 mm thickness worker platform.
- This mat is suitable for general purpose applications.

## 562 Sanitop™ Black

		PRODUCT SPECIFICATIONS		
Designation	Industrial Matting	Industrial Matting		
Туре	Anti-fatigue / anti-slip	Anti-fatigue / anti-slip		
Description	Duckboard, open ring r	Duckboard, open ring mat with bevel edges		
Material	Natural rubber compo	Natural rubber compound		
Process	Compression moulding			
Category	Better			
Recommended use	Heavy duty – wet/dry industrial environments - general applications			
Colours	Black			
Weight	8 kg/m <sup>2</sup>			
Thickness	12.7 mm			
Standard sizes	91 cm x 152 cm, 91 cm x 297 cm, 91 cm x 594 cm			
Custom sizes	N/A			
Special remarks				
		PRODUCT TESTING		
	Tests	Norms	Results	
Foam battery		ASTM D3574		
Abrasion resistance		ASTM D3884-01		
	500 Cycles			
	1000 Cycles		6 % weight loss	
Static coefficient of friction		ASTM C1028-96	0.59	
Elongation		ASTM D412	227.7%	
Breaking load		ASTM D412	37.5 lb	
Graves tear strength		ASTM D 1004		
Hardness		ASTM D2240-02	52 Shore A	
Anti-slip		DIN 51130 and BG-RULE BGR181		
Sanitary epidemiologic test		GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.251.P.044985.07.09	
		MATERIAL ANALYSIS		
Compression Set @25%		ASTM D395	-6.5 %	
Compression deflection @ 25 %		ASTM D575	24.6 lb/in <sup>2</sup>	
Compression deflection@ 50 %		ASTM D575	67.2 lb/in <sup>2</sup>	
F		FIRE TESTING	1	
	Critical radiant flux	ASTM E-648		
		DIN4102		
Fire	Fire retardancy	EN 13501-1		
	Flammability test	ASTM D2859	Pass	
ESD		ANSI ESD S7.1 50% Humidity		
Sustainability		<ul> <li>Recyclable material</li> <li>Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals)</li> </ul>		

DODITOT CDECITIC ATIONS

