


746GR Check'n'Roll™ 3 mm Nitrile



- Ideal flooring for factory and warehouse premises or any industrial applications to protect floors and materials.
- Grease resistant.
- Matting with excellent wear and tear resistance. Used as flooring, shelf liners and in all kinds of industrial applications in workshops, near machines and any place where objects may tend to slide on workbenches, carts, cars or lorry booths.



746GR Check'n'Roll™ 3 mm Nitrile

PRODUCT SPECIFICATIONS		
Designation	Non-directional matting	
Type	Flooring / runner	
Description	Industrial checker plate profile, oil resistant	
Material	Nitrile rubber	
Process	Calendering	
Category	Non-directional pattern	
Recommended use	Factory and warehouse premises or any kind of industrial applications to protect floors and materials.	
Colours	Black	
Weight	51.6 kg per mat	
Thickness	3 mm	
Standard sizes	140 cm x 10 m	
Custom sizes	Per linear meter	
Special remarks	Resistance to temperature : -10°C, +70°C	
PRODUCT TESTING		
Tests	Norms	Results
Compression deflection	U.S.	
	1.4 kg/cm ² 2.8 kg/cm ²	
Foam battery	ASTM D3574	
Abrasion resistance	ASTM D3884-01	
	500 Cycles 5000 Cycles	300 - 500 mm ³
Static coefficient of friction	ASTM C1028-96	
Elongation	ASTM D412	250%
Breaking load	ASTM D412	
Tear strength	ASTM D 1004	7 N/mm ²
Hardness	DIN 53505	65 Shore A
Anti-slip	DIN 51130 and BG-RULE BGR181	
FIRE TESTING		
	Critical radiant flux	ASTM E-648
	Fire retardancy	DIN4102
		EN 13501-1
Flammability test	ASTM D2859	
ESD	ANSI ESD S7.1 50% Humidity	
Sustainability	<ul style="list-style-type: none"> • Polymer content 75 % nitrile rubber • Recyclable material • Reach Compliant (Registration, Evaluation, Authorization and Restriction of Chemicals) 	